

2000 Ltr Fuel Tank

Model: 20TCG



Fuel Tank Data

U.N. (United Nations) Approved IBC (Intermediate Bulk Container) approved for the transport of diesel fuel under the ADR regulations. The Transcube Global is fully bunded (steel in steel) to ensure environmental compliance with Pollution Prevention Guidelines (PPG2).

- Easily Stacked 2 high full, 3 high empty to reduce storage space requirements
- Access manhole for maintenance and inspection of inner tank.
- Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the Transcube Global full of fuel.
- Secure lockable access hatch to house pumps (electric and hand!) And feed and return connections for up to 3 generators.
- Protected galvanised framework preventing damage to tank, paint work and decals.
- Sized to stack inside shipping containers and across truck beds providing economical transportation.

Standard Tank Fittings: 3" Fill Point : 2" Fill Point : Gauge : Pressure Vacuum Vent : Breather Vent : 2 x 1 1/2" Sockets on top of inner tank : 2 x 1 1/2" Sockets on front face of inner tank

Capacity (brim full) Ltrs	2000	Inner Tank Material (thickness)	5235 (3mm)
Capacity (brim full) Gals	440	Weight Unladen (kg)	823
Dimensions	2300 mm (Length)	Weight Laden (kg)	2809
	1150 mm (Width)	Design Approvals	ADR IBC Type 31A
	1320 mm (Height)	Design Standards	Bunded to COP Regulations (PPG2)
Bund Material (thickness)	5235 (3mm)		

Unit B1 Colliery Business Park
Pike Road, Eythorne
Dover, Kent CT15 4FE

t 01304 833900
e rental@powerhire.uk.com
www.powerhire.uk.com

